Abstract

A fluid control device is characterized in that the device is structured of a hollow first fluid path (21) and second fluid path (22), a housing portion (1) formed between the first fluid path and the second fluid path and having a hollow portion with a cross-sectional area larger than cross-sectional areas of both fluid paths, and a valve member (3) that has a main body (31) and a projection portion (32) that are installed in an opening portion where the first fluid path is connected to the hollow portion and that is formed of an elastic material. The fluid control device enables the circulation of liquid when the pressure of liquid flowing from the first fluid path toward the second fluid path is more than a predetermined level. The fluid control device enables accurate and safe measurement of pressure including blood pressure, and, when flushing operation of an infusion circuit etc. is finished, the device enables speedy lowering of pressure to a value that accurately reflects blood pressure of a patient and enables obtaining of a necessary flow rate in a region where pressure is relatively low.

(12)特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関
国際事務局

(43) 国際公開日
2004 年2 月26 日 (26.02.2004)

PCT

(10) 国際公開番号
WO 2004/016314 A1

(51) 国際特許分類[7]: A61M 39/24

(21) 国際出願番号: PCT/JP2003/009930

(22) 国際出願日: 2003 年8 月5 日 (05.08.2003)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:
特願2002-235531 2002 年8 月13 日 (13.08.2002) JP

(71) 出願人 (米国を除く全ての指定国について): 株式会社ジェイ・エム・エス (JMS CO.,LTD.) [JP/JP]; 〒730-8652 広島県 広島市中区 加古町12番17号 Hiroshima (JP).

(71) 出願人 および
(72) 発明者: 橋本 悟 (HASHIMOTO,Satoru) [JP/JP]; 〒615-8191 京都府 京都市西京区 川島有栖川町５９ Kyoto (JP).

(72) 発明者; および
(75) 発明者/出願人 (米国についてのみ): 藤井 亮至 (FUJII,Ryoji) [JP/JP]; 〒730-8652 広島県 広島市中区 加古町12番17号 株式会社ジェイ・エム・エス内 Hiroshima (JP). 澤 健治 (SAWA,Kenji) [JP/JP]; 〒730-8652 広島県 広島市中区 加古町12番17号 株式会社ジェイ・エム・エス内 Hiroshima (JP).

(74) 代理人: 川島 利和 (KAWASHIMA,Toshikazu); 〒171-0022 東京都 豊島区 南池袋2丁目47番7号 サンハイツ池袋501号 Tokyo (JP).

(81) 指定国 (国内): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[続葉有]

(54) Title: FLUID CONTROL DEVICE

(54) 発明の名称: 流体制御装置



(57) Abstract: A fluid control device is characterized in that the device is structured of a hollow first fluid path (21) and second fluid path (22), a housing portion (1) formed between the first fluid path and the second fluid path and having a hollow portion with a cross-sectional area larger than cross-sectional areas of both fluid paths, and a valve member (3) that has a main body (31) and a projection portion (32) that are installed in an opening portion where the first fluid path is connected to the hollow portion and that is formed of an elastic material. The fluid control device enables the circulation of liquid when the pressure of liquid flowing from the first fluid path toward the second fluid path is more than a predetermined level. The fluid control device enables accurate and safe measurement of pressure including blood pressure, and, when flushing operation of a transfusion circuit etc. is finished, the device enables speedy lowering of pressure to a value that accurately reflects blood pressure of a patient and enables obtaining of a necessary flow rate in a region where pressure is relatively low.

[続葉有]

WO 2004/016314 A1